

Monitoring and Managing 4G Network Elements Using Rich UI Frameworks

Sree Lakshmi Addepalli¹, Sree Gowri Addepalli²

Dept., of Computer Engineering, Vivekanand Education Society's Institute Of Technology, Chembur, Mumbai, India^{1,2}

Abstract: Network management systems provides an integrated system for sharing device information across management applications, automation of device management tasks, visibility into the health and capability of the network, and identification and localization of network trouble. By using common centralized systems and network-inventory knowledge, a Network management system delivers a unique platform of cross-functional management capabilities that reduces network administration overhead. An element management system (EMS) consists of systems and applications for managing network elements (NE) on the network element-management layer (NEL) of the Telecommunications (TMN) model. The element management system's key functionality is divided into five key areas - fault, configuration, accounting, performance and security (FCAPS). Portions of each of the FCAPS functionality fit into the TMN models. This paper presents a service delivery platform which aims to develop an enterprise web application that manages these 4G network elements through various modules to meet the required Quality of Service (QoS) using RichFaces framework. RichFaces is an open source Ajax enabled component library for JavaServer Faces which allows easy integration of Ajax capabilities into enterprise application development.

General Terms

SDP - Service Delivery Platform

RAM - Resource Assurance Management

KPI - Key Performance Indicator

EMS - Element Management System

NEL - Network Element Management Layer

NE – Network Elements

TMN – Telecommunications model

FCAPS - Fault, Configuration, Accounting, Performance and Security

Keywords

Element management system (EMS), FCAPS (fault, configuration, accounting performance and security) JavaServer Faces (jsf), RichFaces, JavaEE, JBoss.

1. INTRODUCTION

wireless system with wide area coverage and high throughput. It is designed to be cost effective and to provide high spectral efficiency. The 4g wireless uses Orthogonal Frequency Division Multiplexing (OFDM), Ultra Wide Radio Band (UWB), and Millimeter wireless. Data rate of 20mbps is employed. The high performance is achieved by the use of long term channel prediction, in both time and frequency, scheduling among users and smart antennas combined with adaptive modulation and power control. Frequency band is 2-8 GHz. It gives the ability for worldwide roaming to access cell anywhere. It supports for interactive multimedia, voice, streaming video, Internet, and other broadband services. High speed, high capacity, and low cost per bit Global access, service portability, and scalable mobile services Seamless switching, and a variety of Quality of Service driven services. To provide efficient 4G services there should be proper communication and management between various nodes or network elements. Element management system (EMS) plays an important role here.

4G Fourth generation wireless system is a packet switched An element management system manages one or more of a wireless system with wide area coverage and high specific type of telecommunications network element. throughput. It is designed to be cost effective and to provide high spectral efficiency. The 4g wireless uses within each NE but does not manage the traffic between Orthogonal Frequency Division Multiplexing (OFDM), different NEs in the network.

To support management of the traffic between itself and other NEs, the EMS communicates upward to higher-level network management systems (NMS) as described in the telecommunications management network layered model.

Examples of elements which can be managed through the EMS interfaces are Cable telephony media gateway, Media gateway, Soft switch, Video compression technology provider, Wireless broadband provider, and Smart electricity meters.

EMS/NMS manages information needs like Performance Counters, Alarms and Configuration Parameters of various nodes. To get this information EMS/NMS have various monitoring tools namely:

Copyright to IJARCCE



A. Fault monitoring tool

In network management, fault management is the set of functions that detect, isolate, and correct malfunctions in a telecommunications network, compensate for environmental changes, and include maintaining and examining error logs, accepting and acting on error detection notifications, tracing and identifying faults, carrying out sequences of diagnostics tests, correcting faults, reporting error conditions, and localizing and tracing faults by examining and manipulating database information.

When a fault or event occurs, a network component will often send a notification to the network operator using a protocol such as simple network management protocol (SNMP). An alarm is a persistent indication of a fault that clears only when the triggering condition has been resolved. A current list of problems occurring on the network component is often kept in the form of an active alarm list such as is defined in RFC 3877, the Alarm management information base (MIB). A list of cleared faults is also maintained by most network management systems.

Fault management systems may use complex filtering systems to assign alarms to severity levels. These can range in severity from debug to emergency, as in the syslog protocol. Alternatively, they could use the ITU X.733 Alarm Reporting Function's perceived severity field. This takes on values of cleared, indeterminate, critical, major, minor or warning. It is considered good practice to send a notification not only when a problem has occurred, but also when it has been resolved. The latter notification would have a severity of clear.

A fault management console allows a network administrator or system operator to monitor events from multiple systems and perform actions based on this information. Ideally, a fault management system should be able to correctly identify events and automatically take action, either launching a program or script to take corrective action, or activating notification software that allows a human to take proper intervention (i.e. send email or SMS text to a mobile phone). Some notification systems also have escalation rules that will notify a chain of individuals based on availability and severity of alarm.

B. KPI or Raw counter monitoring tool

Key performance indicators define a set of values used to measure against. These raw sets of values, which are fed to systems in charge of summarizing the information, are called indicators. Indicators identifiable and marked as possible candidates for KPIs can be summarized into the following sub-categories:

• Quantitative indicators that can be presented with a number.

• Qualitative indicators that can't be presented as a Platform – Resource Assurance Management). number.

• Leading indicators that can predict the outcome of a process

n a • Lagging indicators that present the success or for failure post hoc

• Input indicators that measure the amount of resources consumed during the generation of the outcome

• Process indicators that represent the efficiency or the productivity of the process

• Output indicators that reflect the outcome or results of the process activities

• Practical indicators that interface with existing company processes.

• Directional indicators specifying whether or not an organization is getting better.

• Financial indicators used in performance measurement and when looking at an operating index.

A KPI can follow the SMART criteria.

This means the measure has a Specific purpose for the business, it is Measurable to really get a value of the KPI, the defined norms have to be Achievable, the improvement of a KPI has to be Relevant to the success of the organization, and finally it must be Time phased, which means the value or outcomes are shown for a predefined and relevant period.

In order to be evaluated, KPIs are linked to target values, so that the value of the measure can be assessed as meeting expectations or not.

2. SYSTEM DESIGN

A. CONCEPT

The web application is developed to manage and monitor the 4-G network elements using UI Interface and KPI in which we manage and monitor all the nodes which are being used in 4g network, to observe that all the nodes are performing well or whether they need any maintenance work.

If any node is not performing well we can get the reason behind that and can resolve it at the same time.

It'll also display the way to resolve that particular error because in future this application will not be under developer's hand, it will be used by the nontechnical person who may not have the enough knowledge about how to resolve those errors.

It'll create the users, assign role to them, manage the alarms and view the raised alarms, configuring the parameters, view the counters in particular module and creates and modify KPI to display the reports.

Nodes are supported By SDP-RAM (Service Delivery Platform – Resource Assurance Management).






Figure: Context Level Data Flow Diagram

B. IMPLEMENTATION

The web application is a rich, feature-complete GUI for easy operations and maintenance of the network element nodes. The following modules have been worked upon:

1. Login Module

Login Module is a common module as a web based application, where a registered subscriber can login into the SDP-RAM. If user is not registered, an error message is shown in the portal. There is validation over various conditions like login credentials do not match special character validation etc.



Figure 1: Login Module

2. User Module

This module allows the operator to perform user management like creating a new user, modifying a user, viewing details of a user and deleting the user.




Figure 2: User Module

3. Role Module

This module allows the user to create a role, modify, delete and view a particular role of a user or an administrator.

	Element Management Syste		~	
100	SOP Nodes		SDP RAM ROLE	MANAGEMENT
	 Notification Server 	-	V.	
	 RCS Enhanced 	-	Click the tabs to manage roles	
	P-Short Messaging Gateway	-	Crase Badly Vandalate	
	Bocial Networking Platform	-	ROLE NAME *	
	RIS Nodes		ROLE DESCRIPTION */	
	P-CSCF		IT PSNOV	ITI NO.
	s-csc#	-	E elem E Carta Rean El Cauter	E alem El Carla Ream El Cauter
	+ HCSOF	-		
	1 LTE-HSS		III ROSE	E PORCE
	* MS-H25		🖽 Alem 🖽 Carty Param 🖽 Courter	🖾 warm 🔟 Carrig Param 🖾 Courter
-	Converged Charging System		El JOSOF	El SOSCE El siere El Carty Paren El Caurter
	SP-AS	-	ET LTE-HER	EI ROCF
	- BOCP		E nam E Conta form E Courter	E Alem E Carty feam E Cauter
	OTM Server	•	El sevole El Alem El Confg Param El Courter	CHARGING
			🗇 OTH 🗇 Alem 🗇 Certy Reen 🖾 Cauter	III 387-45 III Alem III Conty Ream III Counter
			22 Albertab. 22 Annual 22 Conty Param 22 Counter	는 Rote Management 은 Create Role 은 Delos Role 은 Hostly Role 는 Very Role
			E User Management E Greek Kaar E Dielek Kaar E Heatly Sear E Very Sear	E KPEStanagement E Deale KR E Deale KR E Hardy KR E View KR
			Create Rule	

Figure 3: Role Module

4. Alarm Module

In this module the operator manages the alarms and views the raised alarms. It also clears all minor alarms and individual alarms.

	Server 10.49 16.52 8080				Configuring	Alarms
Alarm Level		Alarm	Level : Minor			
Minor	Alarm 10	Alarm Description	Alern Time Stamp	Alarm Lavel	Remedial Action	Clear Alarm
Major	RtTetalCharge_MINOR_1328	SIP interface initialised Successfully.	Mon Feb 06 16 53 36 (ST 2012	Minor	0	-
Critical	-		4 4			_
Warning						
Indeterminate						

Figure 4: Alarm Module

5. Counter Module

This module allows the user to view the counters in particular node and reset the counter.

and but	Wennesde : aanderen bankt in	managaman 🖉 karves Roses 🛠 managaman 🚨 kog Cel 🕯	(3)
		an en es voro	
	and the second se		(CONTRACTOR)
	Performance Counters	Discourt Add. Discourt annual	
	Participana Consister & Calegory	Enabled Calegory . 1010	Contract States
		and_HTM_ME_anglesed_naml	E Contraction
		past_HTTR_PART_PAT_RECEIPING_Disargen	8
		pres_01700_accesy_clast	8
		control 10, many, but any most	
		LOD. OTTO, AN. AND	
		100,0110,00,000	P
		010.0770.04.0100.000	P
		cont_stTVM_plan_calable_modelsalase	F
		cold_01110_croadd_blod_receiteature	1
		010.0777.000.000	
		and JHTH, Just, Just	
		and offer and including cost	
		Inc. International Concernation	-
		and of the parameters and	
		and a second	
		100,0779,2020,202,202,202,202	
		and_HTTP, researching, aparating, holds, rold	P.
		are, still, are aren, tell	
		cont_HTTP_bacHt_plan_deacts.attus	P
		140, 0777, rearing associety, 3684, 1487	8
		and print party party party and	
		toolloude two tools and	r
		and other and and and and	F
		and prime, and	

Figure 5: Counter Module



6. Configuration Parameter Module

This module allows the user to view the configuration parameter for particular node. This module sets the scalar parameter and tabular parameter.

Product Variant			(mm) (3)
Configuring Parameters	Parameter Same	And State Calegory - communication Personation Values	And in set
AND Configurations discussions			
 N. NOT THE OTHER POST OF A DECEMBER OF A DECEMB OF A DECEMBER OF A DECEM	re service all address from put	luna	10000
We have been thread as a series of the serie	Notest to a Constitute a close Chicagonal	prese .	1000
He has been different, angebrende inter He, han been Agen Constitutionary	IR. Anton of the Public State Commonst	prese .	87788
All had been being ingenet Court Barting	ALL MARTINE AND	press	1000
PE Salitation of Planting	-Riterio Confree Decoment Tenand	passed in the local distance of the local di	ALC: 1
Acuter Configuration Parameter	statistical sectors and a sector of the sector	4.000	E1010
The second se	ALCONOMIC ACTION	14	1000
	In Inclusion and Company	-	ETTER A
	H. Marris M. Million		2 CT10
			and the second sec
	All fait for the Child Charles of the		ALCONG.
			E2228
	18,141111000000000000000000	la.	
	28. No. 10. A STOCK OF COMPANY OF COMPANY		1000
	Photo and a submittee of a longer	14	
	10.20110.01.01.01.000.000.000.000	par.	10000
	of the second second	14	800.00
	and have to also the state of the state of the	(F)	80000
	10,000 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	7	1000
	- A latter that the Market and South States	17	1000
	of the second second second second second		10000
	10.1111011111111111111111111111	100.00.00.00	10000
	No. of Concession, Statement of Concession, Statement	1000	10000
	and shad the set of the state of the state	2444, 446	80000
	- Minister Passant		1000
	denotes an an an an an	presentation	0000
	Restauration for a method of	,	0000
	The base in a division of the same free states and the	*	8000
		A CONTRACTOR OF A	

Figure 6: Configuration Parameter Module

7. KPI Module

This module allows the user to manage the KPI module by performing CRUD operations (Create, Delete, and Update) on the KPI.





C. USING SDP-RAM

The complete SDP infrastructure lies on the underlying JBoss servers. All parts of the SDP viz. customer portal, managed services portal, Telecom services, and instant messaging services are deployed on JBoss Enterprise Application Platform. It contains all the designed modules.

The login page allows the operator login; the user should enter the Username and password in case of invalid username and password appropriate error message will be shown.

The home page allows the operator to view the nodes that are currently up or in existence, the operator can click on an appropriate node icon link in order to perform the respective management related to that node.



Figure 8: Home Page of SDP-RAM

The navigation bar page will give information about the nodes that are supported by SDP-RAM.

Each node name is accompanied by an icon image beside, if the icon is green color it will indicate that currently the corresponding node is alive, further the icon color will turn red when the corresponding node goes down.

Ele	ment Management Syste	∍m
SI	OP Nodes	~
	Notification Server	-
	RCS Enhanced	-
	IP-Short Messaging Gateway	-
==	Social Networking Platform	-
IM	SNodes	~
	P-CSCF	-
	S-CSCF	-
	I-CSCF	-
==	LTE-HSS	-
==	IMS-HSS	-
==	Converged Charging System	-
==	SIP-AS	-
	BGCF	-
==	OTM Server	-

Figure 9: Navigation Page of SDP-RAM

The help page will guide the operator to get information related to server, configuration parameter, performance counter and alarm.

The page includes icons for server help, configuration parameter help, performance counter help and alarm help.

The operator can click on the configuration parameter help link to get an overview about the configuration parameter supported by the node.

The operator can click on the alarm help link to get an overview about the various levels of alarms and the field that it supports.

The operator can click on the performance counter help link to get an overview about the counter supported by the node.



Element Man	agement System	
SDP Nodes		Help - Notification Server
Notificat	ion Server	**
· RCS En	hanced 🛛	
. IP-Shot Gateway	Messaging ·	To get Description of Configuration Reserver; counters and Alarms used in notification server;Click on Conresponding Hep- icon
, Social N Platform	letworking 🔹	
MS Notes		-
· P.CSOF		Notification Server Help Configuration Parameters Help
S-CSOF		
+ HCSOF		
· LTE-HS	8 .	Performance Counters Help Alarms Help
MSHS	s 🔹	Automatice counters nep
Converg System	ed Charging	2 2
SIP-AS		
BGCF		
· OTM Se	tver ·	
Concerned in the		At 112 Annual Annual Technologies Seat wave for Divide Feature 2 0.010, Food 2.2 d with 1024 5 742

Figure 10: Help Page of SDP-RAM

In the user management module the operator will select the user management option and then select the create tab. The operator is required to enter information like username, first name, surname, email-id and assign a role to the user.

The role management page allows the user to navigate through the different section of the Role Management Module. The operator will select the role management option and then select the create tab. In this module the operator can create an appropriate role that can further be assigned to a particular user to restrict the user privileges.

The dashboard page will indicate the operator the number of alive servers that are in existence for the particular node type. This page will show details of the server such as Sever IP, Sever port, timestamp indicating the time when the server came into existence and the status will indicate whether the server is up or down.

		The real			0	rver Room
SDP Nodes	^	70	Notifica	tion Server Room		rver Room
 Notification Ser 						
 RCS Enhanced 	d 📕					
IP-Short Messa Gateway	aging 🗧	Note: This Page will externatically refresh in 5 Seconds. All the active Notification Series are displayed here Please click the corresponding serier which you want to manag				
Social Network Platform	ing 🖕					
IMS Nodes	•	NS Server IP	NS Server Port	NS Server Time, Since Up	STATUS	Go to Manage NS
P-CSCF		10.49.16.52	7070	Wed Apr 18 12:06:12 IST 2012	Î	20
S-CSCF						
I-CSCF						
LTE-HSS						
MS-HSS						
Converged Ch System	arging 🖕					
SIP-AS						
BGCF						
OTM Server						

Figure 11: Dashboard Page of SDP-RAM

The manage page shows icons to perform operations related to Configure Parameter management, Alarm JavaScript Object Notation (JSON). management, Counter management for the node

The configure parameter page allows the user to navigate through the different operations of the Configure Parameter Management Module.

This module allows the operator to view the various configuration parameter related to the particular node.

The alarm page allows the user to navigate through the different operations of the Alarm Management Module. This page allows the operator to view the various alarm levels and the alarms that are raised, this sections gives information about the alarm such as Alarm ID, Alarm description, Alarm timestamp, Alarm level. The operator can clear particular alarm. The operator is also privileged to clear all minor alarms.

The counter page allows the user to navigate through the different operations of the Alarm Management Module. This page allows the operator to view the various alarm levels and the alarms that are raised, this sections gives information about the alarm such as Alarm ID, Alarm description, Alarm timestamp, Alarm level. The operator can clear particular alarm. The operator is also privileged to clear all minor alarms.

3. SYSTEM ENVIRONMENT

A. SDP MANAGEMENT INTERFACES

JBoss Enterprise Application Platform deployed on Red Hat Enterprise Linux plays an extremely critical role in building a state-of-the-art fault tolerant Service Delivery Platform (SDP). It use http, https, and SOAP protocols to achieve web based Operational Goals related to services, subscriber query and order management. SDP supports management from a variety of open interfaces, which can be leveraged for integrating with northbound systems such as Network Management Systems (NMS). The standard open interfaces supported by the SDP are REST (Representational State Transfer) and SOAP (Simple Object Access Protocol).




Figure 12: SDP MANAGEMENT INTERFACES

REST is an abbreviation on Representational State Transfer. REST defines a set of architectural principles by which developer can design Web services that utilize system's resources. REST uses HTTP and is stateless. It exposes directory structure-like URIs and transfers XML,

TECHNOLOGIES USED В.

Java Enterprise Edition 1.

The platform provides an API and runtime environment for developing and running enterprise software, including network and web services, and other large-scale, multitiered, scalable, reliable, and secure network applications.



modular components running on an application server. A access via a request-response programming model. Java EE application server can handle transactions, Although servlets can respond to any type of request, they security, scalability, concurrency and management of the are commonly used to extend the applications hosted by components it is deploying.

Java Server Faces 2.

Java Server Faces is a standard Java framework for building user interfaces for Web applications. It simplifies C. the development of the user interface. Without a comprehensive framework designed for enterprise Web application development, these core technologies can often lead to a variety of development and maintenance problems. Java Server Faces avoids problems by offering a robust, "best of breed" framework with well-established development patterns, built upon the experience of many preexisting Java Web development frameworks.

3. **Rich Faces**

Rich Faces is an open source framework hosted by JBoss that adds Ajax capability into existing JSF applications without resorting to JavaScript. Rich Faces leverages Java Server Faces framework including lifecycle, validation, conversion facilities and management of static and 4G wireless networks not only enable more efficient, dynamic resources. Rich Faces components with built-in Ajax support and a highly customizable look-and-feel can be easily incorporated into JSF applications. Rich Faces is more than just a component library for Java Server Faces. It adds:

Skinability (easily changes and application look and feel).

Component Development Kit (CDK) to assist in constructing Java Server Faces components.

Dynamic Resource Framework and component • based Ajax control components.

4. **RESTful Web Services**

A RESTful web service is a simple web service implemented using HTTP and the principles of REST. It is a collection of resources, with four defined aspects:

The base URI for the web service. •

The Internet media type of the data supported by the web service is often JSON, XML or YAML.

The set of operations supported by the web • service using HTTP methods (e.g., GET, PUT, POST, or DELETE).

The API must be hypertext driven. •

5. AJAX

Asynchronous JavaScript and XML is new web development technique used for the development of most interactive website. Ajax helps in making the web application more interactive by retrieving small amount of data from web server and then showing it on the application without refreshing the page.

Java Server Pages 6.

JSP is a technology that helps software developers create dynamically generated web pages based on HTML, XML, or other document types. To deploy and run Java Server

Pages, a compatible web server with a servlet container, such as Apache Tomcat is required.

7. Servlets

Servlet is a Java programming language class used to extend the capabilities of servers that host applications

Web servers. Thus, it can be thought of as a Java Applet that runs on a server instead of a browser.

DEPLOYMENT

The application is deployed on JBoss Application Server. The JBoss Enterprise Application Platform is a subscription-based/open-source Java EE-based application server runtime platform used for building, deploying, and hosting highly-transactional Java applications and services. Because it is Java-based, the JBoss application server operates cross-platform: usable on any operating system that supports Java. Its Key features support to Java Server Faces (JSF), including Rich Faces and Web application services, including Apache Tomcat for Java Server Pages (JSP) and Java Servlets.

4. CONCLUSION

scalable, and reliable wireless services but also provides wider variety of services. These opportunities come with a need for rethinking our security, privacy, architect and billing technologies that have been used for previous generations. Hence it is very important to manage and update monitor the network elements to enable efficient and reliable services.

REFERENCES

- [1] Network Management System by Douglas W. Stevenson
- Max Katz, Ilya Shaikovsky Practical Rich Faces, 2nd Edition, [2]
- [3] Core Java Server Faces by David Geary (Author), Cay S. Horstmann (Author)
- [4] Head First Servlets & JSP. Second Edition
- [5] refcardz.dzone.com/refcardz/richfaces-40-next-generation
- RESTful Web Services, Leonard Richardson, Sam Ruby [6]
- faces Tutorial, http://www.mastertheboss.com/jboss-[7] Rich web/richfaces/richfaces-4-quick-tutorial
- [8] JavaEE,Documentation, http://www.oracle.com/technetwork/java /javaee/documentation/tutorials-137605.html xadel,htt p:// livedem o.exadel.com/richfaces-demo/index.jsp