IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940



International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193

An Universal Intelligent Assistive Communication and Guidance System (UIACGS)

Dr. Byrareddy C R[1], Chandushree Y M[2], Asha B[3], Goutami C[4], Bhavana S V[5]

Professor, Department of Electronics and Communication, Bangalore Institute of Technology, Bengaluru, Karnataka, India [1]

B.E Student, Department of Electronics and Communication, Bangalore Institute of Technology, Bengaluru, Karnataka, India [2-5]

Abstract: Communication and navigation are major challenges for individuals with hearing, speech, or visual impairments. This paper presents the Universal Intelligent Assistive Communication and Guidance System (UIACGS), a portable assistive solution designed to improve accessibility, independence, and interaction with the surrounding environment. The proposed system integrates intelligent sensing, embedded processing, audio-visual feedback, and assistive technologies to support users in their daily activities. It incorporates speech-based interaction, visual information assistance, obstacle awareness, and currency recognition to provide practical support in different real-world situations. An display presents essential information, while integrated hardware modules process input signals and deliver appropriate responses through accessible output mechanisms. The system is designed with a user-friendly interface, compact hardware architecture, and affordable components to make assistive technology more accessible. The developed prototype demonstrates how multiple supportive functions can be combined into a single device rather than relying on separate solutions. The implementation focuses on improving communication, providing environmental guidance, and supporting everyday tasks for people with different accessibility requirements. The proposed approach highlights the potential of intelligent embedded systems in developing inclusive, portable, and cost-effective assistive devices. Its effectiveness depends on sensor performance, recognition reliability, environmental conditions, and the accuracy of individual modules.

Keywords: Universal Assistive Technology; Intelligent Communication; Embedded Systems; Accessibility; Speech Assistance; Obstacle Awareness; Currency Recognition; Visual Assistance; Portable Guidance Device.

I. INTRODUCTION

A. Background and Motivation

Assistive technology plays an important role in improving the independence, accessibility, and quality of life of individuals with hearing, speech, or visual disabilities. People facing communication and mobility difficulties often depend on others to perform routine activities, understand their surroundings, and access essential information. Existing assistive solutions frequently address individual problems through separate devices, making them difficult to manage and less convenient for everyday use.

The Universal Intelligent Assistive Communication and Guidance System (UIACGS) addresses these challenges by integrating multiple supportive functionalities into a single portable device. The proposed system combines intelligent embedded technology, sensor-based interaction, speech assistance, obstacle awareness, currency recognition, and visual information . These features are intended to help users communicate more effectively, recognize surrounding obstacles, access important information, and perform common daily activities with greater convenience.

The effectiveness of the proposed device depends on the coordination of its hardware components, processing capabilities, and output mechanisms. Integrating different assistive functions into one compact platform provides a practical approach to reducing dependence on multiple individual devices. This motivates the development of an affordable, user-friendly, and intelligent solution that promotes independent living, improves everyday communication, and supports inclusive accessibility for people with different disabilities.

 This work is licensed under a Creative Commons Attribution 4.0 International License



International Journal of Advanced Research in Computer and Communication Engineering
Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026
DOI: 10.17148/IJARCCE.2026.151193

B. Problem Statement

Individuals with hearing, speech, or visual impairments often experience difficulties in communication, understanding their surroundings, identifying obstacles, and accessing essential information during everyday activities. The objective of the proposed Universal Intelligent Assistive Communication and Guidance System (UIACGS) is to develop an integrated portable device that addresses these challenges through intelligent embedded technology and assistive functionalities.

The proposed system combines speech assistance, obstacle detection, currency recognition, and visual information display to support users in different real-world situations. Sensor inputs and processing modules are used to recognize environmental conditions and provide appropriate feedback through accessible output mechanisms. The OLED display presents relevant information, while audio-based responses assist users in understanding system outputs.

The system is designed as an integrated assistive solution rather than requiring individuals to depend on multiple independent devices. Its primary objective is to improve communication, increase environmental awareness, and support independent daily activities through a compact, affordable, and user-friendly platform. The overall performance depends on recognition accuracy, sensor reliability, processing efficiency, and the effectiveness of feedback provided to the user.

C. Research Objectives

1. To develop a Universal Intelligent Assistive Communication and Guidance System that supports individuals with hearing, speech, and visual impairments in performing everyday activities.
2. To integrate speech assistance, obstacle detection, currency recognition, and visual information display into a single portable assistive device.
3. To implement intelligent hardware and embedded processing techniques for collecting, analysing, and responding to user inputs and environmental conditions.
4. To provide accessible feedback through audio-based responses, enabling users to understand information and interact with their surroundings effectively.
5. To evaluate the developed prototype in terms of functionality, response time, recognition accuracy, sensor reliability, affordability, and its potential to improve independent living.

D. Research Contributions

The proposed work presents the development of the Universal Intelligent Assistive Communication and Guidance System (UIACGS), an integrated assistive device designed to improve accessibility and independence for individuals with hearing, speech, and visual impairments. First, it combines multiple assistive functionalities, including speech assistance, obstacle detection, currency recognition, and visual information display, within a single portable platform. Second, it integrates sensor-based monitoring, embedded processing, and intelligent recognition techniques to collect environmental information and generate suitable responses for users. Third, the system incorporates audio feedback and display to deliver essential information through accessible communication methods. Furthermore, the proposed device focuses on reducing dependence on multiple individual assistive tools by providing several supportive features within one compact solution.

The developed prototype demonstrates the practical integration of hardware components and intelligent functionalities for everyday assistance.

II. LITERATURE REVIEW

A. Existing Assistive Technology Approaches

Assistive technologies have been developed to improve the independence and accessibility of individuals with visual, hearing, and speech impairments. Traditional solutions include walking sticks, electronic navigation aids, speech-assistance applications, and wearable devices. Recent developments have introduced electronic systems that combine sensors, embedded controllers, and audio feedback to support users during everyday activities. These technologies help individuals identify surrounding objects, communicate information, and perform routine tasks with reduced dependence on others.

Existing research on assistive systems highlights the importance of combining different sensing and feedback techniques to improve accessibility. Reviews of assistive technologies describe the use of ultrasonic sensors, computer vision, speech processing, and audio-based guidance for supporting individuals with visual impairments [1], [2]. However, many existing solutions concentrate on a particular function, such as navigation, object identification, or communication, instead of providing multiple assistive services through one integrated device.

The proposed Universal Intelligent Assistive Communication and Guidance System (UIACGS) addresses this limitation by bringing different assistive functionalities together within a portable platform. It focuses on providing communication

 This work is licensed under a Creative Commons Attribution 4.0 International License

DOI: 10.17148/IJARCCE.2026.151193

assistance, obstacle awareness, currency recognition, and accessible information through audio and visual feedback mechanisms.

B. Sensor-Based Obstacle Detection and Guidance Systems

Sensor-based obstacle detection is an important technology used in electronic mobility aids for visually impaired individuals. Several existing systems employ ultrasonic sensors to measure the distance between the user and nearby objects. These sensors operate using ultrasonic sound waves and determine object distance by measuring the time taken for the transmitted signal to return after reflection. The measured distance can then be compared with a predefined threshold to identify potentially dangerous obstacles.

Previous research has demonstrated the use of Raspberry Pi controllers, HC-SR04 ultrasonic sensors, and audio feedback for developing smart belts and electronic walking aids [3]. Such systems provide alerts when an obstacle is detected within a specified range. Other research reviews have also identified ultrasonic sensing and acoustic feedback as commonly used techniques in wearable obstacle-avoidance systems [2].

Although these approaches provide useful assistance, their effectiveness can be affected by sensor positioning, detection range, environmental conditions, and the presence of moving objects. The proposed UIACGS uses sensor-based obstacle detection as one of its major functionalities. It aims to process distance measurements and provide suitable alerts through its output mechanisms, helping users become more aware of nearby obstacles.

C. Image Processing and Speech-Based Communication Technologies

Image processing and speech-processing techniques play an important role in developing intelligent assistive devices. Image processing enables electronic systems to capture and analyse visual information using cameras. Common operations include image acquisition, resizing, noise removal, colour conversion, feature extraction, and image comparison. These techniques can be applied to currency recognition by analysing the visual characteristics of currency notes and identifying their corresponding denominations.

Speech-processing technologies provide another important method of interaction for individuals with communication difficulties. Speech-to-text (STT) techniques convert spoken input into textual information, whereas text-to-speech (TTS) techniques generate spoken responses from text. These methods enable users to communicate with electronic devices through audio-based interaction. Existing research on assistive systems identifies speech recognition and text-to-speech as important technologies for improving accessibility [4], [5].

In the proposed UIACGS, image-based processing supports currency recognition, while speech-based interaction provides communication assistance. An display is incorporated to present relevant information visually, and audio feedback is used to communicate system responses. These combined techniques aim to provide alternative methods of accessing information and interacting with the device. The actual recognition algorithm and speech-processing software depend on the modules and programs used in the implemented prototype.

D. Research Gap and Proposed System Approach

Existing assistive technologies provide various solutions for individuals with visual, hearing, and speech impairments, including obstacle detection devices, speech-assistance applications, currency recognition systems, and electronic navigation aids. However, most of these solutions focus on individual requirements rather than combining multiple assistive functionalities into a single portable device. Depending on separate devices for communication, obstacle awareness, and everyday object recognition can increase complexity, cost, and inconvenience for users. Furthermore, certain existing solutions face limitations related to detection accuracy, environmental conditions, accessibility, and ease of operation.

The proposed Universal Intelligent Assistive Communication and Guidance System (UIACGS) aims to address these limitations by integrating speech assistance, sensor-based obstacle detection, currency recognition, based information display into one compact platform. By combining embedded processing, image-processing techniques, and audio-visual feedback, the system provides multiple forms of assistance through a unified device. The research focuses on developing an affordable, user-friendly, and practical solution that supports communication, improves environmental awareness, and encourages greater independence in everyday activities.

III. SYSTEM DESIGN AND PROBLEM FORMULATION

A. System Components and Hardware Description

The proposed Universal Intelligent Assistive Communication and Guidance System (UIACGS) is designed as an integrated electronic assistive device using Raspberry Pi 5 as its central processing unit. The hardware architecture consists of a camera module, an obstacle detection sensor, a start/stop control button, and a relay module. The camera captures visual information from the environment in front of the user, while the sensor collects distance measurements

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940

International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193

to identify nearby obstacles. The Raspberry Pi 5 receives these inputs and coordinates the overall system operation. The start/stop button provides manual control, whereas the relay module acts as an interface for controlling an external alert or output device. These components work together to provide visual recognition and environmental awareness through a single portable platform.


B. Input Acquisition and Processing

The system obtains information through two primary input mechanisms: camera-based image acquisition and sensor-based distance measurement. The camera continuously captures images of the front surroundings when the system is activated. These images are transferred to the Raspberry Pi 5 for further processing and identification of humans, objects, and currency notes. The obstacle detection sensor independently measures the distance between the device and nearby objects. The received sensor readings are processed using predefined distance conditions to determine whether an obstacle is present within the specified detection range. Both input sources provide complementary information for the system's decision-making process.

C. Recognition and Detection Formulation

The proposed system performs visual recognition and obstacle detection to assist users in understanding their surrounding environment. Let I represent the image captured by the camera and d represent the distance measurement obtained from the obstacle detection sensor. The visual processing unit analyses the captured image to identify the presence of humans, surrounding objects, and currency denominations. The sensor processing unit evaluates the measured distance against a predefined threshold. An obstacle condition is identified when the measured distance falls within the configured detection range.

The overall system decision is based on the information received from both processing units. Camera-based recognition provides information about the visual contents of the environment, whereas sensor-based detection provides distance-related information about nearby obstacles. The system does not generate artificial currency values or estimated object distances; instead, it processes the actual camera and sensor inputs to produce corresponding recognition and detection results.



D.Control Logic and System Operation

The system operation is controlled by the Raspberry Pi 5 through its GPIO interfaces. Initially, the user activates the device using the start button, enabling the camera and sensor modules. The captured images and measured distances are processed independently, and the resulting information is evaluated by the system control logic. When a programmed detection condition is satisfied, the Raspberry Pi 5 generates an appropriate control signal for the relay module. The relay switches the connected external output device according to the implemented control conditions. The stop button allows the user to terminate the operating process. This coordinated operation provides a simple mechanism for integrating visual recognition, obstacle awareness, and hardware-based control within a single assistive device.

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940



International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193

IV. PROPOSED METHODOLOGY

A. System Overview

The proposed Universal Intelligent Assistive Communication and Guidance System is designed to assist visually impaired individuals by identifying objects and obstacles in their surroundings. The system uses a Raspberry Pi 5 as its central processing unit, which receives visual information from the camera and distance-related information from the sensor.

The camera captures the real-time surroundings, while the sensor detects nearby obstacles. The Raspberry Pi 5 processes the received information to identify humans, commonly encountered objects, currency and other obstacles. Based on the detection results, the system controls the connected alert mechanism through a relay module to provide assistance to the user.

The start/stop button allows the user to activate or deactivate the system whenever required.

B. Hardware Input Acquisition

The input acquisition stage collects information from the surrounding environment using the camera and sensor.

1. Camera: Captures real-time images and video of the objects present in front of the user.
2. Sensor: Detects nearby obstacles and provides distance-related information to the Raspberry Pi 5.
3. Start/Stop Button: Allows the user to start and stop the complete system.
4. Raspberry Pi 5: Receives the camera and sensor inputs and coordinates the processing operations.

C. Image Processing and Object Detection

The Raspberry Pi 5 acts as the central processing unit of the system. It processes the camera input using the implemented image-processing and object-detection software.

The system identifies different categories of objects, including:

- Human Detection: Identifies people present in front of the user.
- Object Detection: Recognizes commonly encountered objects in the surroundings.
- Currency Detection: Identifies currency notes using the implemented detection model.
- Obstacle Detection: Identifies objects that may obstruct the user's path.

The sensor provides additional distance information to help determine whether an obstacle is nearby. The camera-based detection and sensor readings together support the system's environmental awareness.

D.Alert and Assistive Response

The final stage provides an alert based on the detected objects and obstacles.

1. The Raspberry Pi 5 evaluates the information received from the camera and sensor.
2. When an object or obstacle is detected, the system processes the detection result.
3. The Raspberry Pi 5 controls the relay module according to the programmed conditions.
4. The relay module switches the connected alert mechanism to provide an indication to the user.

The system continues monitoring the surroundings while it is active. When the stop button is pressed, the monitoring operation is stopped.

E. Working Flow Diagram

1. System activation: The user presses the Start button. The Raspberry Pi 5 activates the system. The Stop button terminates monitoring.

2. Data acquisition: The camera captures the surroundings, and the sensor collects nearby-obstacle or distance information.

3. Processing and detection: The Raspberry Pi 5 processes the camera input and identifies humans, supported objects, currency and obstacles. Sensor readings provide additional information about nearby obstacles.


4. Decision and response: The system evaluates the detection results. If an alert condition is identified, the Raspberry Pi 5 activates the relay module according to the programmed conditions. The relay controls the connected alert mechanism. Otherwise, the system continues monitoring.

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940

International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193



V. SYSTEM IMPLEMENTATION

A. Image Processing and Object Detection

The image-processing module is implemented using a camera connected to the Raspberry Pi 5. The camera continuously captures real-time images of the environment in front of the user when the system is activated.

The captured images are processed by the object-detection software running on the Raspberry Pi 5. The system is designed to recognize different categories of objects, including:

- Human Detection: Identifies humans present in front of the user.
- Object Detection: Recognizes commonly encountered objects in the surrounding environment.
- Currency Detection: Identifies currency notes to assist users in recognizing money.
- Obstacle Detection: Identifies obstacles that may affect the user's movement.

B. Hardware and Software Integration

The hardware and software components are integrated through the Raspberry Pi 5, which acts as the central controller of the proposed system.

The camera and sensor are connected to the Raspberry Pi 5 to provide real-time environmental information. The captured images are processed using the implemented detection software, while the sensor provides obstacle-related readings. The Start/Stop button is used to control the operation of the system. When the Start button is pressed, the Raspberry Pi 5 initiates the monitoring process. The camera and sensor begin supplying information for processing. When the Stop button is pressed, the monitoring process is terminated.

The relay module is interfaced with the Raspberry Pi 5 to control the connected alert mechanism. This integration enables the system to coordinate object detection, obstacle monitoring and alert operations.

C. Alert Management and Output Generation

The alert management module evaluates the information obtained from the image-processing and sensor modules. When a human, object, currency note or obstacle is detected, the system processes the corresponding detection result. For obstacle-related conditions, sensor readings are also considered to determine whether an alert should be generated. Based on the programmed conditions, the Raspberry Pi 5 controls the relay module. The relay switches the connected alert mechanism to provide an indication to the user. The system continues monitoring the environment while it remains active. If no alert condition is identified, the monitoring process continues. When the Stop button is pressed, the system stops its operation. This approach provides a coordinated method of environmental monitoring, object recognition and assistive response.

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940



International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193

VI. EXPERIMENTAL SETUP AND EVALUATION

A. Experimental Configuration

The experimental setup consists of hardware and software components integrated with the Raspberry Pi 5. The Raspberry Pi 5 acts as the central processing unit and coordinates the camera, sensor, detection software and relay module.

The camera is positioned to capture the environment in front of the user. The sensor is connected to detect nearby obstacles and provide distance-related information. The Start/Stop button is used to control the operation of the system.

The captured images are processed by the Raspberry Pi 5 to identify humans, objects and currency notes. The sensor readings are used along with camera information for obstacle monitoring. Based on the programmed conditions, the Raspberry Pi 5 controls the relay module to activate the connected alert mechanism.

B. Experimental Testing Procedure

The system is tested under different environmental conditions to verify the operation of its individual components and the complete system.

The following experiments are considered:

1. Human Detection Test: A person is placed in front of the camera to verify whether the system can identify human presence.
2. Object Detection Test: Different commonly encountered objects are placed within the camera's field of view to evaluate object recognition.
3. Currency Detection Test: Currency notes are presented in front of the camera to verify currency identification.
4. Obstacle Detection Test: Obstacles are placed at different distances to examine the sensor's ability to detect nearby objects.
5. Start/Stop Operation Test: The buttons are tested to verify that the system starts and stops correctly.
6. Relay Operation Test: The relay module is tested to verify whether it responds correctly to the programmed alert conditions.

C. System Evaluation Metrics

The performance of the proposed system is evaluated using different parameters to understand its detection capability, response and operational reliability.

The following evaluation metrics are considered:

- Detection Accuracy: Measures how correctly the system identifies the intended humans, objects and currency notes.
- Obstacle Detection Performance: Evaluates the ability of the sensor to detect nearby obstacles.
- Response Time: Measures the time taken by the system to process an input and generate the corresponding response.
- System Reliability: Evaluates whether the system operates consistently during repeated testing.
- Relay Response: Verifies whether the relay module activates according to the programmed conditions.

D. Validation and Test Protocol

The validation process is carried out to verify the functionality of the integrated hardware and software components.

The system is tested by placing different objects, currency notes and human subjects in front of the camera. Sensor readings are checked by placing obstacles at different distances. The Start/Stop button and relay module are also tested independently and as part of the complete system.

The following validation steps are considered:

1. Verify that the camera captures the surroundings correctly.
2. Check whether the detection software recognizes the supported object categories.
3. Verify whether the sensor detects nearby obstacles.
4. Check whether the Raspberry Pi 5 processes the inputs correctly.
5. Verify whether the relay activates under the programmed alert conditions.
6. Repeat the experiments to check consistent system operation.

The experimental observations are recorded to evaluate the overall performance of the system. Any incorrect detections, missed obstacles or delayed responses are noted for further improvement.


 This work is licensed under a Creative Commons Attribution 4.0 International License

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940

International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193



VII. RESULTS AND DISCUSSION

A. Object Detection Performance

The camera-based object detection module is designed to identify different categories of objects present in front of the user. The Raspberry Pi 5 processes the captured images using the implemented detection software.

The system focuses on four major detection categories: human detection, common object detection, currency detection and obstacle identification.

The detection performance is evaluated by comparing the number of correctly identified objects with the total number of test samples.

The accuracy of the detection system is calculated using:

\[Accuracy(\%)=\frac{TP+TN}{TP+TN+FP+FN}\times100 \]

Where:

- TP – True Positive
- TN – True Negative
- FP – False Positive
- FN – False Negative

B. Obstacle Detection Performance

The obstacle detection module uses a sensor connected to the Raspberry Pi 5 to identify nearby obstacles and obtain distance-related information.

During testing, obstacles are placed at different distances in front of the sensor. The measured distance is compared with the actual distance to evaluate the sensor's performance.

The system uses the sensor readings to identify nearby obstacles and determine whether an alert condition should be generated.

The evaluation considers:

- Accuracy of obstacle detection.
- Difference between actual and measured distance.
- Consistency of sensor readings.
- Response to obstacles placed at different distances.

This module is important because it helps the user become aware of nearby obstacles and supports safer movement.

IJARCCE ISSN (O) 2278-1021, ISSN (P) 2319-5940

International Journal of Advanced Research in Computer and Communication Engineering

Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026

DOI: 10.17148/IJARCCE.2026.151193

C. System Response and Alert Evaluation

The response performance of the proposed system depends on the processing capability of Raspberry Pi 5 and the interaction between the camera, sensor and relay module. When the camera identifies an object or the sensor detects an obstacle, the Raspberry Pi 5 evaluates the received information according to the programmed conditions. If an alert condition is identified, the Raspberry Pi 5 controls the relay module to activate the connected alert mechanism. The response time is evaluated by measuring the time between receiving the input and generating the corresponding output. The Start/Stop button is also tested to verify the proper activation and deactivation of the system. These experiments help evaluate the responsiveness of the system and the coordination between its hardware components.

D. Integrated System Performance

The integrated system is evaluated by examining the combined operation of the hardware and software modules. The camera captures the surroundings, while the sensor provides additional obstacle-related information. The Raspberry Pi 5 processes these inputs and performs the programmed detection operations The relay module responds according to the detection and alert conditions. The Start/Stop button provides control over the complete monitoring process. The integration of these components provides a centralized approach to environmental monitoring and assistive guidance.

The overall evaluation focuses on:


1. Successful communication between the camera, sensor and Raspberry Pi 5.
2. Correct execution of the implemented detection operations.
3. Proper activation of the relay module.
4. Reliable operation of the Start/Stop button.
5. Continuous monitoring while the system remains active.

E. Error Analysis and Limitations

Although the proposed system provides an integrated approach to object recognition and obstacle detection, its performance may be affected by different environmental and operational conditions.
Some important limitations include:

- Lighting Conditions: Poor lighting may affect the quality of captured images and object recognition.
- Object Occlusion: Partially hidden objects may be difficult to identify correctly.
- Detection Errors: Similar-looking objects may lead to incorrect classifications.
- Sensor Limitations: Sensor readings may vary depending on obstacle position, surface and environmental conditions.
- Processing Delay: Complex image processing may increase response time depending on the detection model and processing workload.

These limitations indicate areas where further improvements can be made to enhance detection accuracy, response time and system reliability.



DOI: 10.17148/IJARCCE.2026.151193

F. Error Analysis and Limitations

1. The proposed Universal Intelligent Assistive Communication and Guidance System may produce inaccurate or delayed responses due to incomplete user inputs, AI processing errors, or unstable internet connectivity. Real-time communication and guidance also depend on the availability and reliability of connected services.
2. Other limitations include challenges in supporting multiple languages and different user needs, ensuring data privacy and security, and maintaining reliable real-time updates. Further improvements in AI accuracy, accessibility, scalability, and real-world testing are required to make the system more effective and reliable.

VIII. CONCLUSION AND FUTURE WORK

The proposed Universal Intelligent Assistive Communication and Guidance System provides an intelligent solution for assisting users in understanding their surrounding environment through real-time detection. The system uses Raspberry Pi 5 as its main processing unit, integrated with a camera, sensor, start/stop button and relay module. These hardware components work together to capture environmental information, process inputs and perform the required detection operations.

The camera captures images of the surroundings, while the sensor helps identify nearby obstacles. The Raspberry Pi 5 processes the captured information to detect humans, common objects, currency and other obstacles in front of the user. The start/stop button provides control over system operation, and the relay module is used to control the connected circuit based on the system's output.

Overall, the proposed system demonstrates the application of embedded computing and intelligent detection techniques in assistive technology. It aims to improve environmental awareness and support safer movement by identifying objects and obstacles in real time. The integration of these components provides a foundation for developing an affordable, portable and effective assistive guidance system.

A. Future Work

Future improvements will focus on enhancing the accuracy, reliability and efficiency of the proposed Universal Intelligent Assistive Communication and Guidance System. The existing detection models can be further optimized to improve the identification of humans, common objects, currency and obstacles under different environmental conditions. Special attention can be given to low-light conditions, crowded places, varying object distances and different camera angles. The processing speed of Raspberry Pi 5 can also be improved through model optimization and efficient image-processing techniques to achieve faster and more accurate real-time detection.

The system can be further enhanced by integrating voice-based announcements and audio guidance to communicate detected objects, currency denominations and nearby obstacles to users. Multilingual voice support can also be introduced to make the system accessible to people who speak different languages. Additionally, improvements in sensor technology can provide more reliable obstacle detection and distance measurement. These enhancements can make the system more interactive and useful in different real-world environments.

Furthermore, future development can focus on improving the portability, power efficiency and overall hardware design of the system. A compact design with improved battery backup can make the device more convenient for continuous daily use. Additional testing can be conducted in indoor and outdoor environments to evaluate detection accuracy, response time and overall system performance. By incorporating these improvements, the proposed system can be developed into a more reliable, user-friendly and cost-effective assistive technology solution that supports independent movement and improves environmental awareness.

REFERENCES

[1]. R. Parvadhavardhni, P. Santoshi, and A. M. Posonia, “Blind Navigation Support System using Raspberry Pi & YOLO,” in *Proc. 2nd International Conference on Applied Artificial Intelligence and Computing (ICAAIC)*, 2023, pp. 1323–1329. doi: 10.1109/ICAAIC56838.2023.10140484.

[2]. “Object Detection and Identification for Visually Impaired,” in *Proc. 2nd International Conference on Networking and Communications (ICNWC)*, 2024. doi: 10.1109/ICNWC60771.2024.10537275.

[3]. “An Indian Currency Recognition Model for Assisting Visually Impaired Individuals,” in *Proc. IEEE International Conference on Recent Advances in Systems Science and Engineering (RASSE)*, 2022. doi: 10.1109/RASSE54974.2022.9989624.



International Journal of Advanced Research in Computer and Communication Engineering
Impact Factor 8.471 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 15, Issue 11, November 2026
DOI: 10.17148/IJARCCE.2026.151193

[4]. M. Singh, J. Chauhan, M. S. Kanroo, S. Verma, and P. Goyal, "IPCRF: An End-to-End Indian Paper Currency Recognition Framework for Blind and Visually Impaired People," *IEEE Access*, vol. 10, pp. 90726–90744, 2022. doi: 10.1109/ACCESS.2022.3202007.

[5]. S. Ikram, I. S. Bajwa, S. Gyawali, A. Ikram, and N. M. Alsubaie, "Enhancing Object Detection in Assistive Technology for the Visually Impaired: A DETR-Based Approach," *IEEE Access*, vol. 13, pp. 71647–71661, 2025. doi: 10.1109/ACCESS.2025.3558370.

[6]. "VisionAid: A Smart Assistive Device for Both Navigation and Medication," in *Proc. 3rd International Conference on Intelligent Cyber Physical Systems and Internet of Things (ICoICI)*, 2025. doi: 10.1109/ICoICI65217.2025.11254430.

[7]. "YOLO-v3 Based Currency Detection and Recognition System for Visually Impaired Persons," in *Proc. International Conference on Contemporary Computing and Applications (IC3A)*, 2020. doi: 10.1109/IC3A48958.2020.233314.

[8]. "Bridging the Perception Gap: A YOLO V8 Powered Object Detection System for Enhanced Mobility of Visually Impaired Individuals," in *Proc. First International Conference on Technological Innovations and Advance Computing (TIACOMP)*, 2024. doi: 10.1109/TIACOMP64125.2024.00028.